



All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

According to

IEC 60169-16, MIL-PRF-39012, CECC 22210

Documents

Assembly instruction

53 P

Panel piercing

B 12

Material and plating

Connector parts

Center contact

Material

CuBe

Plating

AuroDur®, gold plated

Outer contact

Brass

Flash white bronze over silver(e.g. Optargen®)

Body

Brass

Flash white bronze over silver(e.g. Optargen®)

Dielectric

PTFE

Crimping ferrule

Copper

Flash white bronze over silver(e.g. Optargen®)

Electrical data

| | |
|--|---|
| Impedance | 50 Ω |
| Frequency | DC to 11 GHz |
| Return loss | ≥ 25 dB, DC to 2.5 GHz ≥ 20 dB, 2.5 to 6 GHz |
| Insertion loss | ≤ 0.05 dB, DC to 6 GHz |
| Insulation resistance | ≥ 5 x10 ³ MΩ |
| Center contact resistance | ≤ 1 mΩ |
| Outer contact resistance | ≤ 0.25 mΩ |
| Working voltage | 500 V rms |
| Power handling (at 20 °C, sea level, VSWR 1.0) | 1000 W @ 1 GHz 700 W @ 2 GHz |
| RF-leakage | ≥ 128 dB up to 1 GHz |

- Limitations are possible due to the used cable type -

Mechanical data

| | |
|----------------------|------------------|
| Mating cycles | min. 500 |
| Coupling test torque | max. 1.7 Nm |
| Recommended torque | 0.7 Nm to 1.1 Nm |

Environmental data

| | |
|---------------------|---------------------------------|
| Temperature range | -55°C to +155°C |
| Thermal shock | MIL-STD-202, Meth. 107, Cond. B |
| Corrosion | MIL-STD-202, Meth. 101, Cond. B |
| Vibration | MIL-STD-202, Meth. 204, Cond. B |
| Shock | MIL-STD-202, Meth. 213, Cond. I |
| Moisture resistance | MIL-STD-202, Meth. 106 |
| RoHS | compliant |

Tooling

| | |
|---------------|------------|
| Crimping tool | 11W150-000 |
| Crimp insert | 11W150-208 |

Suitable cables

RG 58 C/U, RG 141/U

Weight

| | |
|--------|------------|
| Weight | 36.1 g/pce |
|--------|------------|

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

| Draft | Date | Approved | Date | Rev. | Engineering change number | Name | Date |
|--|----------|-------------|----------|------|--|-------------|---------------|
| Inge Mühlauer | 08/06/04 | J_Gramsamer | 15.04.15 | f00 | 15-0397 | J_Krautenb. | 15.04.15 |
| Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de | | | | | Tel.: +49 8684 18-0 email: info@rosenberger.de | | Page 2 / 2 |