



MATERIALS:

1. GUIDE TRAY - GLASS FILLED POLYBUTYLENE TEREPHTHALATE, STATICALLY DISSIPATIVE, 94V-0, BLACK
2. SHIELD - ZINC DIECAST, CLEAR CHROMATE FINISH
3. DB-9 RECEPTACLE
SHELL: STEEL WITH TIN PLATE
INSULATOR: GLASS FILLED PBT, UL94V-0
CONTACTS: PHOSPHOR BRONZE, 30 MICRO GOLD OVER NICKEL UNDERPLATE
4. ADAPTER CAN BE STACKED SIDE TO SIDE ON A 1.5 INCH MINIMUM SPACING.

WITHOUT SERIAL IDENTIFICATION	73086-0001
DESCRIPTION	PART NUMBER

MFC. SH. REV.	REMOVE P/N PER UOI 2000-0151 99/08/09 DSL	REVISIONS	DIMENSIONS SHOWN (METRIC) INCH		
	D		APP'D. MJM	UNLESS OTHERWISE SPECIFIED TOLERANCES: ANGULAR 1/2°	
				DRWG. BY RKN	CHK'D. BY DLD
				SCALE 2:1	
LTR.			FILE NAME S73086X1.DGN		

REVISE ONLY ON CAD SYSTEM	
TITLE GBIC ADAPTER COPPER, DB-9, PASSIVE	
PART NO. SEE CHART	DRWG. NO. SDA-73086-001
MOLEX INCORPORATED LISLE, ILL. 60532 U.S.A.	SHEET NO. 1 OF 1 DATE 98/05/20
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.	
DIV. D	SIZE B