



General Description

The MAX3622 evaluation kit (EV kit) is an assembled demonstration board that provides convenient evaluation of the MAX3622 low-jitter, precision clock generator. The EV kit includes a 25MHz crystal on-board to allow immediate testing.

The kit includes switches to allow easy control of the enable/disable functions. The clock outputs use SMA connectors and are AC-coupled to simplify connection to test equipment.

Ordering Information

PART	TYPE
MAX3622EVKIT	EV Kit

Features

- ◆ AC-Coupled I/Os for Ease of Testing
- ◆ Fully Assembled and Tested
- ◆ +3.3V Power-Supply Operation
- ◆ 25MHz Crystal Included On-Board

Component Suppliers

SUPPLIER	WEBSITE
NDK	www.ndk.com

Component List

DESIGNATION	QTY	DESCRIPTION
C1, C3, C4, C5, C11, C13, C14, C18, C19	9	0.1µF ±10% ceramic capacitors (0402)
C2	1	10µF ±10% ceramic capacitor (0603)
C6, C17, C20	3	0.01µF ±10% ceramic capacitors (0402)
C7	1	4.7pF ±5% ceramic capacitor (0402)
C9	1	33pF ±10% ceramic capacitor (0402)
C10	1	27pF ±10% ceramic capacitor (0402)
J1, J3, J5	0	Not installed
J2, J48	2	Test points
J4	1	2-pin header, 0.1in. centers

DESIGNATION	QTY	DESCRIPTION
J6, J7, J18	3	SMA connectors
L1	1	2.7µH inductor
R1, R2	2	150Ω ±5% resistors (0402)
R3	1	36Ω ±5% resistor (0402)
R4	1	499Ω ±1% resistor (0402)
R5, R6	0	Not installed
R11	1	10.5Ω ±1% resistor (0402)
SW1, SW2	2	SPDT switches
TP6, TP7	2	Test points
U1	1	MAX3622CUE+
Y1	1	25MHz crystal
None	1	NDK EXS00A-AT00429
None	1	Shunt
None	1	PCB: MAX3622 Board, Rev A

**Evaluates:
MAX3622**

MAX3622 Evaluation Kit

Quick Start

To evaluate the MAX3622, configure the EV kit as follows:

- 1) Determine which output is going to be evaluated and connect to the test equipment through an SMA cable(s).
- 2) Connect a +3.3V power supply to J48 (VCC) and J2 (GND). Set the current limit to 200mA.
- 3) Enable the output under test by setting the related output-enable switch high.

- 4) The clock frequency at the LVCMS output (QA_C) is 125MHz. The clock frequency at the LVPECL output is 156.25MHz.
- 5) Note that when the LVCMS output is being evaluated, the amplitude seen on 50Ω test equipment is attenuated by the on-board circuitry. The voltage swing is approximately one-twelfth of what would be seen by directly connecting QA_C to a high-impedance input.

Table 1. Adjustment and Control Descriptions (see Quick Start first)

COMPONENT	NAME	FUNCTION
J4	INDUCTOR	J4 shunts the power-supply inductor. Normal operation is J4 shunted.
SW1	QB_OE	Set high to enable LVPECL output QB. Set low to force a logic zero at QB.
SW2	QAC_OE	Set high to enable LVPECL output QA. Set low to force a logic zero at QA.

Evaluates: MAX3622

MAX3622 Evaluation Kit




Figure 1. MAX3622 EV Kit Schematic

Evaluates: MAX3622

MAX3622 Evaluation Kit




Figure 2. MAX3622 EV Kit Assembly Drawing—Top Side




Figure 3. MAX3622 EV Kit Layout—Component Side

Evaluates: MAX3622

MAX3622 Evaluation Kit




Figure 4. MAX3622 EV Kit Layout—Ground Plane




Figure 5. MAX3622 EV Kit Layout—Power Plane

MAX3622 Evaluation Kit

Evaluates: MAX3622




Figure 6. MAX3622 EV Kit Layout—Solder Plane




Figure 7. MAX3622 EV Kit Assembly Drawing—Bottom Side



Microsemi Corporate Headquarters
One Enterprise, Aliso Viejo CA 92656 USA
Within the USA: +1 (949) 380-6100
Sales: +1 (949) 380-6136
Fax: +1 (949) 215-4996

Microsemi Corporation (NASDAQ: MSCC) offers a comprehensive portfolio of semiconductor solutions for: aerospace, defense and security; enterprise and communications; and industrial and alternative energy markets. Products include high-performance, high-reliability analog and RF devices, mixed signal and RF integrated circuits, customizable SoCs, FPGAs, and complete subsystems. Microsemi is headquartered in Aliso Viejo, Calif. Learn more at www.microsemi.com.

© 2012 Microsemi Corporation. All rights reserved. Microsemi and the Microsemi logo are trademarks of Microsemi Corporation. All other trademarks and service marks are the property of their respective owners.