

LISA2-RS-PIN

~19° spot beam. 6.8 mm high variant with location pin installation.


TECHNICAL SPECIFICATIONS:

Dimensions	Ø 9.9 mm
Height	6.8 mm
Fastening	glue, pin
Colour	black
Box size	310 x 230 x 60 mm
Box weight	1.4 kg
Quantity in Box	2000 pcs
ROHS compliant	yes ⓘ



MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour
LISA2-RS	Lens	PMMA	clear
LISA2-HLD-PIN	Holder	PC	black



INDEX	PART NO	DESCRIPTION	MATERIAL	COLOUR
1	F10989	LISA2-HLD-PIN	PC	black
2	-	LISA2_lens	PMMA	

Tolerances if not otherwise shown
 According to DIN ISO 2768-1
 Linear measures:
 up to 30mm class M, otherwise class C
 According to DIN ISO 2768-2
 Form and position: class L



Ledil Oy
 Salorankatu 10
 FIN 24240 SALO
 Finland

THIRD ANGLE PROJECTION:

DRAWING TITLE
Lisa2-PIN-XP assembly

This drawing is the property of LEDiL Oy. It may not be reproduced, copied or communicated without a written agreement with LEDiL Oy.


SIZE	PART NUMBER
A4	-

SCALE	4:1	WEIGHT	0,5 g	SHEET	1/1
-------	-----	--------	-------	-------	-----


PHOTOMETRIC DATA (MEASURED):





LED XP-E
 FWHM 16.0°
 Efficiency 90 %
 Peak intensity 6.500 cd/lm
 Required components:





LED XP-G
 FWHM 24.0°
 Efficiency 90 %
 Peak intensity cd/lm
 Required components:



LED XQ-E HI
 FWHM 11.0°
 Efficiency 86 %
 Peak intensity 11.500 cd/lm
 Required components:




LED LUXEON C
 FWHM 16.0°
 Efficiency 87 %
 Peak intensity 6.800 cd/lm
 Required components:



PHOTOMETRIC DATA (MEASURED):



LUMILEDS

LED LUXEON Z ES
FWHM 15.0°
Efficiency 84 %
Peak intensity 6.600 cd/lm
Required components:





NICHIA

LED NCSxE17A
FWHM 13.0°
Efficiency 72 %
Peak intensity 4.300 cd/lm
Required components:



SAMSUNG

LED LH181B
FWHM 16.0°
Efficiency 71 %
Peak intensity 3.100 cd/lm
Required components:




SHARP

LED Double Dome (GM2BB)
FWHM 18.0°
Efficiency 90 %
Peak intensity cd/lm
Required components:


PHOTOMETRIC DATA (SIMULATED):




LED XQ-E
 FWHM 14.5°
 Efficiency 91 %
 Peak intensity 10.100 cd/lm
 Required components:




LED Oslon Square EC
 FWHM 18.0°
 Efficiency 90 %
 Peak intensity 5.600 cd/lm
 Required components:



LED Oslon SSL 150
 FWHM 16.0°
 Efficiency 92 %
 Peak intensity 9.040 cd/lm
 Required components:



LED Oslon SSL 80
 FWHM 16.0°
 Efficiency 90 %
 Peak intensity 7.490 cd/lm
 Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)