

# Product Information

## MX6028GL Series

Compliant with IEC61850-3 and IEEE1613  
28G-Port Rackmount Layer 3 Full Gigabit  
Managed Ethernet Switches



### Features

- ❖ Supports RIP, OSPF, layer 3 routing protocols
- ❖ 24 Gigabit Ethernet ports
- ❖ Up to 28 optical fiber connections (SFP slots)
- ❖ Fanless, -40 to +85°C operating temperature range
- ❖ Universal 110/220VADC power supply range

## Introduction

Process automation and transportation automation applications combine data, voice, and video, and consequently require high performance and high reliability. The MX6028GL series full Gigabit backbone switches are equipped with 24 x Gigabit Copper Port and 4 x Gigabit SFP Slots. They provide Layer 3 routing functionality to facilitate the deployment of applications across networks and make them ideal for large scale industrial networks. The MX6028GL's full Gigabit capability increases bandwidth to provide high performance and quickly transfer large amounts of video, voice, and data across a network. The switches support the RingOn and RSTP redundancy protocols, and are fanless and come with an isolated redundant power supply to increase system reliability and the availability of your network backbone.

## Specifications

<b>Technology</b>		<b>Switch Properties</b>	
Standard :	IEEE802.3, 802.3u, 802.3ab, 802.3z, 802.3x, 802.1D, 802.1w, 802.1Q, 802.1p	L3 Host table :	4K
Flow Control :	IEEE802.3x Flow Control, Back Pressure Flow Control	MAC Table Size :	16K
Protocols :	IGMP Snooping, GMRP, SNMPv1/v2c/v3, DHCP Client, HTTP, HTTPS, Telnet, NTP Client	Priority Queues :	8
		Max. Number VLANs :	256
		VLAN ID Range :	VID 1 to 4094
		IGMP Groups :	1000
		<b>Interface</b>	
		RJ45 Port :	10/100/1000M Auto-Negotiation, Full/Half Duplex, Auto-MDI/MDIX
		Fiber Port :	100BaseFX (SC/ST connector) and 1000BaseSFP Slot
		LED Indicators :	Power, Port Status, 10/100/1000M
		Console port :	RJ45 Port
		Output Warning :	Relay, Standard 2 Pin
		<b>Power Requirements</b>	
		Input Voltage :	48VDC @ 50W MAX 120~370VDC @ 50W MAX 85~265VAC @ 50VA MAX
		Input Connection :	Grid panel terminal blocks Standard 4 pin input connection (optional)
		<b>Physical Characteristics</b>	
		Case :	Slim Metal Case, IP40 Design
		Dimensions :	443×44×310mm
		Installation :	Rack mounting
		<b>Optical Fiber</b>	
		Mode	Single Mode
		Transmission Distance	20km
		Centre Wavelength	1310nm
		Cable Size	9/125um
		TX Power(dBm)	-8~-2dBm
		RX Power(dBm)	< -24dBm
		Transmission Rate	1000Mbps
		<b>Environment Limits</b>	
		Operating Temp. :	Wide Temp. Models: -40 to 85°C
		Storage Temp. :	-40 to 85°C
		Ambient Relative Humidity :	5 to 95%(Non-condensing)
	<b>L3 Functions</b>		
	<ul style="list-style-type: none"> <li>• Static IP routing</li> <li>• OSPFv1/v2</li> <li>• RIPv1/v2</li> <li>• VRRP</li> <li>• IGMP v2/v3 Multicast Listener Protocol</li> <li>• Firewall , NAT and port mapping</li> <li>• File sharing based on the SAMBA service</li> <li>• FTP service based on STUPID-FTP</li> <li>• SSH secure access service based on OPENSCH</li> <li>• Add access, control WEB</li> </ul>		
	<b>L2 Functions</b>		
	<ul style="list-style-type: none"> <li>• IEEE 802.1Q Static VLAN and VLAN Label</li> <li>• Link Layer Management Protocol (LLDP)</li> <li>• IEEE 802.1w Rapid Spanning Tree Protocol (RSTP)</li> <li>• IGMP SNOOPING</li> <li>• RingOn™ Redundant Technology, recovery time &lt;15ms</li> <li>• RingOpen Redundancy</li> </ul>		
	<b>Management Tools</b>		
	<ul style="list-style-type: none"> <li>• Web Interface (HTTP and HTTPS)</li> <li>• Console port and Command Line Interface(CLI) controlled by SSHv2</li> <li>• SNMPv1/v2c/v3</li> <li>• Flexible configuration and log file management</li> <li>• Managing local file through HTTP, FTP, TFTP and SCP</li> <li>• Syslog(System log file and remote syslog server)</li> <li>• SNTP(NTP Client)</li> <li>• Software Online Upgrading</li> </ul>		
Software functions :			

Standards and Certifications	
EMI :	FCC Part15, CISPR(EN55022) Class A
EMS :	EN61000-4-2(ESD) Level 4, EN61000-4-3(RS) Level 4, EN61000-4-4(EFT) Level 4, EN61000-4-5(Surge) Level 4, EN61000-4-6(CS) Level 4, EN61000-6-2
Shock :	IEC 60068-2-27
Freefall :	IEC 60068-2-32
Vibration :	IEC 60068-2-6

Warranty	
Warranty Period :	3 years

## Ordering Information

### MX6028GL Series

MX6028GL-4SFP-2VLW	Layer 3 Rackmount Managed, 24 x Gigabit Copper Port, 4 x Gigabit SFP Fiber Port, Industrial Wide Temperature -40°C to +85°C, Power Input 48VDC
MX6028GL-4SFP-VHW	Layer 3 Rackmount Managed, 24 x Gigabit Copper Port, 4 x Gigabit SFP Fiber Port, Industrial Wide Temperature -40°C to +85°C, Power Input 120~370VDC or 85~264VAC
MX6028GL-28SFP-2VLW	Layer 3 Rackmount Managed, 28 x Gigabit SFP Fiber Port, Industrial Wide Temperature -40°C to +85°C, Power Input 48VDC
MX6028GL-28SFP-VHW	Layer 3 Rackmount Managed, 28 x Gigabit SFP Fiber Port, Industrial Wide Temperature -40°C to +85°C, Power Input 120~370VDC or 85~264VAC